





Depending on structural conditions, you can choose between high and low landing level safety gates to ensure safe loading and unloading at landing levels.







### ▷ Innovations

- Know-how
- Up-to-date production technologies







ORIGINA

**GEDA**<sup>®</sup> MULTILIFT P18







# GEDA® World-wide competence

# 

### Your GEDA-Dealer:




### **GEDA-Dechentreiter** GmbH & Co.KG

Mertinger Straße 60 D-86663 Asbach-Bäumenheim Phone +49 (0) 906 9809-0 Fax +49 (0) 906 9809-50 info@geda.de www.geda.de




## Personnel and material hoist

### **Platform versions:**



Landing level safety gate



Landing level safety gate

← 1.4 m →



An ingenious system: can be used on all GEDA rack and pinion hoists from 300 kg to 2,000 kg load capacity.

Work economically and flexibly in future with just one mast system!



The 1.5 metre mast sections are easy to put together and are secured with captive bolts and secured nuts.







MULTILIFT P18 Load capacity

Persor Materia Lifting Lifting

Powe

apacity	
	20 persons
al	2000 kg
height	100 m
speed	32 m/min.
supply	2 x 3.7/7.5 kW/400 V/50 Hz



The GEDA Multilift P18 puts every advantage at your disposal:

Compact, pre-installed base unit comprising: car, base enclosure, flat cable bin and drive **O** 

- **No foundations necessary**
- Modular system



- 1 Unloading the base unit with the crane.
- 2 Installing the mast sections from the car.
- Ideal for interior work:
  The enormous loading
  volume makes it possible
  to transport bulky materials
  (e.g. gypsum plasterboard).
- 4 Optional:
  - Level pre-selection in car
  - Level pre-selection
    at all levels